



LED SIGNAGE BACK LIGHITNG





Features

- Adopts high bright 2835LED
- Wide view angle to 165 degree and helps eliminate wasted light
- Constant current, max 40pcs in series connection
- Waterproof IP65 tested
- Low voltage 12VDC system
- 5-years warranty

Application /

- 5-8cm signage lighting box or channels
- 5-8cm lighting box

BLUEVIEW ELEC-OPTIC TECH CO.,LTD



BV-ST12B

LED SIGNAGE BACK LIGHITNG


Specifications

Part No.	BV-ST12B
Input Vol.	12V DC
Power/pc	1.2 W
Lumen/pc	104-107lm
Led Type	SMD2835
CRI	≥85
Max QTY/serie	40pcs
Dimension (LxWxH)	33.5x28.5x7.2mm

Color Available







BLUEVIEW ELEC-OPTIC TECH CO., LTD

Tel: +86-28-8148 0011Fax: +86-28-8148 1258Mail: sales@blueviewled.comWeb.: www.blueviewled.comAdd: No.1000, Section 2, 2nd Konggang Road, SouthwestAviation Industrial Development Zone, Chengdu, Sichuan, China.Zip code: 610207


Specifications are subject to change without notice. © Blueview™ 2017– All rights reserved. Made in China.





LED SIGNAGE BACK LIGHITNG

Luminous Intensity Distribution Diagram








Thickness	Distance (x,y)	Qty/ m²	Illumination
5cm	7x7cm	13x13pcs	5040-8520lux
6cm 8x8cm		11x11pcs	4150-6660lux
7cm	9x9cm	10x10pcs	3470-5220lux
8cm	10x10cm	9x9pcs	3080-4150lux





LED SIGNAGE BACK LIGHITNG





Notes:

- 1. Packaged by anti-static bag and carton
- 2. Outer carton dimension: 570*375*285mm
- 3. 40pcs for one string
- 4. Above-mentioned quantity and weight are only based on above packing method

Product size	Carton Size	Carton	Net Weight	Gross Weight
(mm)	(mm)	(pcs)	(kg)	(kg)
BV-ST12B	570*375*285	2000	22.4(1±10%)	

BLUEVIEW ELEC-OPTIC TECH CO., LTD